

DATA SHEET

Synchronous Alternator



Customer	:	Notes:
Customer reference	:	
Product line	: AG10-250SI20AI	Product code : 14418606
Area classification	: Safe	1010265624

General data Frame (IEC) : 250 Insulation Class : 180°C (H) Total Harmonic Distortion (no load) : ≤ 3% Stator winding pitch : 2/3 Altitude : up to 1000 m.a.s.l Number of Leads : 12 Power factor : 0.8 to 1.0 Excitation system : Brushless with Auxiliary Coil Cooling : IC01	Degree of protection : IP23 Mounting style : B35T Number of poles : 4 Type of Pole : Salient Nominal rotation - 50 Hz : 1500 rpm Nominal rotation - 60 Hz : 1800 rpm Overspeed : 2250 rpm Alternator mass : 730 kg Overload : 1.1x In per 1h each 6h Momentary Overload : 1.5x In per 30s
---	--

Frequency and number of phases		50 Hz								60 Hz											
		3ph				1ph				3ph								1ph			
Voltages (V)	Y connection	380		400		415		-		380		416		440		480		-			
	YY connection	190		200		208		-		190		208		220		240		-			
	Δ connection	220		230		239		-		220		240		254		277		-			
	ΔΔ connection	110		115		120		-		110		120		127		138		-			
	Zig-zag or single phase delta	-		-		-		190 - 200		-		-		-		-		220 - 240			
Output power (kVA)	ΔT=80°C (Ta=40°C)	200		200		190		115.5		205		223		234		250		135.1			
	ΔT=105°C (Ta=40°C)	229		229		217		132.2		235		255		268		288		155			
	ΔT=125°C (Ta=40°C)	250		250		237		144.3		260		278		292		312		169			
	ΔT=150°C (Ta=40°C)	260		260		247		150		275		298		315		345		182			
	ΔT=163°C (Ta=27°C)	277		277		263		160		290		312		330		360		188			
Electrical data (FP=0.8 / ΔT=125°C / Ta=40°C)	Saturated reactances values																				
	Xd(%) Dir. axis synchronous reactance	490.0		415.6		357.4		653.3		593.3		516.4		482.0		428.29		642.7			
	X'd(%) Dir. axis transient reactance	18.7		15.9		13.6		24.93		22.6		19.7		18.4		16.34		24.5			
	X''d(%) Dir. axis subtrans. reactance	13.5		11.4		9.8		18.0		16.4		14.2		13.2		11.68		17.6			
	Xq(%) Quad. axis sync. reactance	135.5		114.9		98.8		180.65		164.1		142.8		133.3		118.43		177.7			
	X''q(%) Quad. axis subtrans. react.	10.8		9.2		7.9		14.4		13.1		24.6		10.6		9.35		14.1			
	X2(%) Negative sequence reactance	17.5		14.9		12.8		23.38		21.2		19.4		17.2		15.27		23.0			
	X0(%) Zero sequence reactance	2.2		1.9		1.6		3.0		2.7		2.4		2.2		1.95		2.9			
	T'd(ms) Short Circ.Trans.time const.	67.6		57.3		48.1		90.09		81.8		66.9		66.5		59.06		88.6			
	T''d(ms) Short Circ. Sub. time const.	1.8		1.5		1.3		2.37		2.1		1.8		1.8		1.55		2.3			
	T'do(ms) Open Circ. time const Trans	1347		1143		960		1796.6		1632		1334		1326		1177.8		1767			
	T''do(ms) Open Circ. time const Subt	2.4		2.1		1.7		3.25		3.0		2.4		2.4		2.13		3.2			
	Ta(ms) Armature time const.	11		9		8		14.91		14		11		11		9.77		15			
	uc(V) Full load excitation voltage	61.3		63.0		68.0		68.1		53.3		57.8		55.8		58.15		55.8			
	ic(A) Full load excitation current	3.7		3.8		4.1		4.09		3.2		3.5		3.4		3.5		3.4			
	ic(A) No load excitation current	0.7		0.8		0.9		0.95		0.6		0.7		0.7		0.87		0.9			
	Icc(A) Sustained Short-Circ. Current	1140		1083		989		1082.53		1185		1129		1149		1125.83		1054			
Kcc Short-circuit ratio	0.44		0.38		0.28		0.59		0.54		0.48		0.44		0.39		0.58				
Efficiency (%)	Power factor	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0		
	25% of load	91.7	93.5	91.9	93.7	92.3	94.1	84.4	86	92.2	93.7	92.2	93.8	92.2	93.8	92	93.7	84.8	86.3		
	50% of load	93	94.7	93.1	94.8	93.5	95.2	85.5	87.1	93.4	94.9	93.5	95	93.7	95.1	93.5	95.1	86.2	87.5		
	75% of load	92.4	94.4	92.7	94.6	93.1	95	85	86.8	92.9	94.6	93.1	94.8	93.3	94.9	93.3	95	85.8	87.3		
	100% of load	91.6	93.7	92	94.1	92.4	94.4	84.2	86.2	92	93.9	92.3	94.2	92.6	94.4	92.8	94.6	85.2	86.9		
	125% of load	90.6	92.9	91.1	93.4	91.5	93.8	81.2	83.7	90.9	93.2	91.3	93.5	91.5	93.6	92	94	84.2	86.2		

Other characteristics Air flow : 1.38 m³/s Exciter stator winding resistance at 20°C : 12.17 ohm Stator winding resistance at 20°C : 0.01858 ohm Rotor winding resistance : 1.13 ohm Stator winding layers : 2 Inertia WR² : 2.36 kgm² NDE Bearing : 6314 2RS DE bearing : 6316 2RS Flange : SAE 2 Coupling disc : WITHOUT	Automatic voltage regulator Accuracy (stability) : +/- 0.5% Rated current : 5 A Analog input : Yes Digital input : No Peak current : 7 A/10 s Droop / TC : Yes Dynamic recovery : 8 to 500 ms U/F : Yes Internal voltage adjustment : +/- 15% External voltage adjustment : +/- 10% Transient recovery time for ΔU=20% : 500 ms	According to: IEC 60034 NBR 5117 NEMA MG1 VDE530 ISO 8528 CSA
---	---	--

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page
Checked by				Revision
Date				1 /